

Fiber Optic Patch Cord G657B3

Features

- Ceramic Ferrule
- High Return Loss
- Low Insertion Loss
- Good Repeatability and Exchangeability
- Excellent Polished and 100% Tested

Applications

- CATV
- Optical Fiber Communication
- Systems Data Transmission Fiber
- Building Network Access
- Cabling, ODF
- FTTX Applications



Description

- Fiber Optic Patch Cord and Pigtail are important for optical network. These are used to be installed at the end of the fiber optic cable.
- The Fiber Optic Patch Cord and Pigtail series comes with a comprehensive collection of lengths and connectors to fulfill every demand.

| Item | SM (Single Mode) | | | | |
|-----------------------------|------------------|-------|-------|-------|------|
| Fiber Cable Type | G657B3 | | | | |
| Fiber Diameter (um) | 9/125 | | | | |
| Cable OD (mm) | 3.0 | | | | |
| End Face Type | РС | UPC | APC | UPC | UPC |
| Typical Insertion Loss (dB) | <0.2 | <0.15 | <0.2 | <0.1 | <0.1 |
| Return Loss (dB) | >45 | >50 | >60 | / | |
| Insert-Pull Test (dB) | <0.2 | | <0.3 | <0.15 | |
| Interchangeability (dB) | <0.1 | | <0.15 | <0.1 | |
| Anti-Tensile Force (N) | >70 | | | | |
| Temperature Range (°C) | -40~+80 | | | | |



WWW.T2TEK.NET info@t2tek.net p.(305)602.2237